

Lumenis Global Sales Offices

America

Santa Clara, CA

Tel + 1 408 764 3000
+ 1 877 586 3647
Fax + 1 408 764 3999
+ 1 800 505 1133

Europe, Middle East & Africa

Dreieich-Dreieichenhain,
Germany

Tel + 49 6103 8335 0
Fax + 49 6103 8335 300

Formello (RM), Italy

Tel + 39 06 90 75 230
Fax + 39 06 90 75 269

London, UK

Tel + 44 20 8324 4200
Fax + 44 20 8324 4222

Asia-Pacific

Beijing, China

Tel + 86 10 6510 2620
Fax + 86 10 6510 2621

Gurgaon, India

Tel + 91 124 422 33 80
Fax + 91 124 422 33 83

Japan

Tokyo, Japan

Tel + 81 3 5789 8300
Fax + 81 3 5789 8310

Internet: www.lumenis.com

Email: information@lumenis.com

CUSTOM FIBERS AND ACCESSORIES

DuoTome™ SideLite™: This single-use fiber is especially well suited for HoLAP.

SlimLine™, SlimLine EZ™ & SlimLine GI™: These reusable and single-use fibers are custom designed to work seamlessly with the VersaPulse family and are perfectly suited for procedures such as HoLEP and stones.

VersaCut™ Morcellator: This system provides rapid and efficient endoscopic removal of resected prostate tissue from the bladder after the HoLEP procedure.

UNPARALLELED SUPPORT, TRAINING AND SERVICE

Lumenis is committed to providing quality products, training and service.

- Fully-trained team of certified service professionals
- Proven customer satisfaction
- World class preceptor program and training tools
- Excellent references including thought leaders

| | Single Wavelength: Holmium | | | Dual Wavelength: Holmium & Nd:YAG |
|-----------------------------------|---|---|---|---|
| | 20 Watt | 60 Watt | 100 Watt | 80/100 Watt |
| Wavelengths | 2.1 microns | 2.1 microns | 2.1 microns | 2.1/1.06 microns |
| Repetition Rate | 5-20 Hz | 5-40 Hz | 5-50 Hz | 5-40 Hz |
| Energy per Pulse | 2J/10 Hz | 1.5J/40 Hz | 2J/50 Hz | 2J/40 Hz |
| Max. Tissue Effect Setting | 120V, 50/60 Hz, 15A Single Phase 220V, 50/60 Hz, 10A Single Phase | 230V, 50/60 Hz 30A Single Phase | 230V, 50/60 Hz 30A Single Phase | 230V, 50/60 Hz 30A Single Phase |
| Electrical | 120V, 50/60 Hz, 15A Single Phase 220V, 50/60 Hz, 10A Single Phase | 230V, 50/60 Hz 30A Single Phase | 230V, 50/60 Hz 30A Single Phase | 230V, 50/60 Hz 30A Single Phase |
| Dimensions | 19" x 24" x 45" (48 cm x 61 cm x 114 cm) | 18" x 36" x 39" (46 cm x 91 cm x 99 cm) | 18" x 36" x 39" (46 cm x 91 cm x 99 cm) | 18" x 36" x 39" (46 cm x 91 cm x 99 cm) |
| Aiming Beam | 2.5 mW at 650 nm, 3 intensity settings, constant and blinking modes | 2.5 mW at 650 nm, 3 intensity settings, constant mode | 2.5 mW at 650 nm, 3 intensity settings, constant mode | 2.5 mW at 650 nm, 3 intensity settings, constant mode |
| Data Output | Printer Output | None | None | None |
| Weight | 185 lbs/84 kg | 340 lbs/155 kg | 340 lbs/155 kg | 340 lbs/155 kg |
| Pulse Duration | Up to 600 microseconds | | | |
| Cooling | Cooling self-contained water-to-air exchanger | | | |
| Delivery Systems | More than 20 reusable and single-use, flexible and rigid, with standard SMA connector | | | |
| Warranty | One year parts and labor | | | |



¹ AUA guidelines for BPH, 2003 - http://www.auanet.org/content/guidelines-and-quality-care/clinical-guidelines/main-reports/bph-management/chapt_1_appendix.pdf; EAU guidelines for BPH, 2005 - http://www.uroweb.org/fileadmin/tx_eauguidelines/2009/Pocket/BPH.pdf; New ureteral stone guidelines reflect treatment changes - Urology Times, Jan 2008, Vol. 36, No. 1.